



D1: \_\_\_\_\_

A1: \_\_\_\_\_

D2: \_\_\_\_\_ TOL: \_\_\_\_\_

A2: \_\_\_\_\_

D2 DIA. CUTTING:  YES  NO

HELIX ANGLE: 30°

D3: \_\_\_\_\_ TOL: \_\_\_\_\_

NO. OF FLUTES: \_\_\_\_\_

D4: \_\_\_\_\_ TOL: \_\_\_\_\_

COOLANT FEED:  YES  NO

L1: \_\_\_\_\_

L2: \_\_\_\_\_ TOL: \_\_\_\_\_

COATING: \_\_\_\_\_

L3: \_\_\_\_\_ TOL: \_\_\_\_\_

MAT'L BEING CUT: \_\_\_\_\_

L4: \_\_\_\_\_ TOL: \_\_\_\_\_

DRILLING DEPTH Lmax: \_\_\_\_\_

***TYSON TOOL***®

TYSON TOOL COMPANY LIMITED

DIMENSIONS NOT SHOWN TO BE TYSON TOOL STANDARDS.  
TOLERANCES ARE BEFORE ANY COATING IS APPLIED.

Appr. By: \_\_\_\_\_

Date: \_\_\_\_\_

Notes:

Title:

**DOUBLE MARGIN SPIRAL  
FLUTE TWO STEP DRILL**

Customer: \_\_\_\_\_

Dwg. No.: \_\_\_\_\_