



D1: \_\_\_\_\_  
 D2: \_\_\_\_\_ TOL: \_\_\_\_\_  
 D3: \_\_\_\_\_ TOL: \_\_\_\_\_  
 L1: \_\_\_\_\_  
 L2: \_\_\_\_\_ TOL: \_\_\_\_\_  
 L3: \_\_\_\_\_ TOL: \_\_\_\_\_  
 RAD: \_\_\_\_\_ TOL: \_\_\_\_\_

CHAMFER ANGLE: \_\_\_\_\_ LENGTH: \_\_\_\_\_ TOL: \_\_\_\_\_  
 SPIRAL:  R/H  L/H  STR  
 CUT:  R/H  L/H  
 HELIX ANGLE: \_\_\_\_\_  
 NO. OF FLUTES: \_\_\_\_\_

COATING: \_\_\_\_\_

MAT'L BEING CUT: \_\_\_\_\_

***TYSON TOOL***®

TYSON TOOL COMPANY LIMITED

DIMENSIONS NOT SHOWN TO BE TYSON TOOL STANDARDS.  
 TOLERANCES ARE BEFORE ANY COATING IS APPLIED.

Appr. By: \_\_\_\_\_

Date: \_\_\_\_\_

Notes:

Title:

**HIGH PERFORMANCE  
 END MILL WITH NECK**

Customer: \_\_\_\_\_

Dwg. No.: \_\_\_\_\_